

THREE PHASE STRING INVERTER 25-40 KW

CSI-25K-T400 | CSI-30K-T400
CSI-33K-T400 | CSI-36K-T400 | CSI-40K-T400

Canadian Solar's grid-tied, transformer-less string inverters help to accelerate the use of three-phase string architecture for commercial rooftop and small ground-mount applications. An NRTL approved, cost-effective alternative to MLPE, these inverters are modular design building blocks that provide high yield and enable significant BoS cost savings. They provide up to 98.8% conversion efficiency, a wide operating range of 180-1000 V_{DC}, and 4 MPPTs for maximum energy harvest.




standard warranty, extension up to 20 years

KEY FEATURES

- Maximum efficiency of 98.8%, Maximum EU efficiency of 98.3%
- 4 MPPTs to achieve higher system efficiency
- Strings intelligent monitoring, Smart I-V Curve Diagnosis supported
- Up to 30% DC input oversize, 13A input for each PV string

EFFICIENCY CURVE

CSI-40K-T400GL02-E



For detailed information, please refer to the Installation Manual.

CSI SOLAR CO., LTD.

199 Lushan Road, SND, Suzhou, Jiangsu, China, 215129 www.csisolar.com

HIGH RELIABILITY

- Advanced thermal design and convection cooling
- Built-in over-voltage and over-current protection
- DC reverse polarity and AC short circuit protection
- Fuse free design

BROAD ADAPTIBILITY

- IP65 rated for outdoor application
- Utility interactive controls: Active power derating, reactive power control and over frequency derating
- Wide MPPT range for flexible string sizing
- High switching frequency and ultra fast MPPT for maximum efficiency over a wide load range

CSI SOLAR CO., LTD. is committed to providing high quality solar products, solar system solutions and services to customers around the world. No. 1 module supplier for quality and performance/price ratio in IHS Module Customer Insight Survey. As a leading PV project developer and manufacturer of solar modules with over 55 GW deployed around the world since 2001.

SYSTEM/TECHNICAL DATA

MODEL NAME	CSI-25K-T400GL02-E	CSI-30K-T400GL02-E	CSI-33K-T400GL02-E	CSI-36K-T400GL02-E	CSI-40K-T400GL02-E
DC INPUT					
Max. DC Input Voltage	1100 V _{DC}				
Start-up DC Input Voltage/Power	180 V _{DC}				
Number of MPP Trackers	3			4	
MPPT Voltage Range	200 - 1000 V _{DC}				
Max. Input Current (Imp)	78 A (26 A per MPPT)			104 A (26 A per MPPT)	
Max. Short Circuit Current (Isc)	120 A (40 A per MPPT)			160 A (40 A per MPPT)	
Number of DC Inputs	6 (2 per MPPT)			8 (2 per MPPT)	
DC Switch	Integrated				
AC OUTPUT					
Rated AC Output Power	25 kW	30 kW	33 kW	36 kW	40 kW
Max. AC Output Power	27.5 kW	33 kW	36.3 kW	39.6 kW	44 kW
Rated Output Voltage*	400 V _{AC}				
Grid Connection Type	3 W / N / PE				
Rated Grid Output Current	36 A	43.3 A	47.6 A	51.9 A	57.7 A
Max Output Current	41.8 A	50.2 A	55.1 A	60.2 A	66.9 A
Rated Output Frequency	50 / 60 Hz				
Output Frequency Range*	47 - 52 / 57 - 62 Hz				
Power Factor	> 0.99 (0.8 leading ... 0.8 lagging)				
Current THD	< 3%				
DC Injection Current	< 0.5 % of Rated Grid Output Current				
SYSTEM					
Max. Efficiency	98.8 %				
EU Efficiency	98.3 %				
Night Consumption	< 1 W				
Anti-PID Module	Optional				
ENVIRONMENT					
DC / AC SPD	DC SPD Type II / AC SPD Type II (Type I Optional)				
Protection Degree	IP65				
Cooling	Natural Convection Cooling				
Operating Temperature Range	- 25 °C to + 60 °C				
Storage Temperature Range	- 40 °C to + 70 °C				
Operating Humidity	0 - 100 % Condensing				
Operating Altitude	4000 m				
Audible Noise	< 30 dBA @ 1 m				
DISPLAY AND COMMUNICATION					
Display	LCD, 2 × 20 Z				
Communication	RS485 / WIFI Optional				
MECHANICAL DATA					
Dimensions (W / H / D)	647 x 629 x 252 mm				
Weight	39.3 kg			45.4 kg	
Installation Angle	0 - 15 Degrees from Vertical				
DC Inputs	MC4				
SAFETY					
Safety and EMC Standard	IEC 62109-1/2, IEC 61000-6-1/2/3/4				
Grid Standard	IEC 62116, IEC 61727				

*The "Rated Output Voltage Range" and "Output Frequency Range" may differ according to specific grid standard.

The specifications and key features contained in this datasheet may deviate slightly from our actual products due to the on-going innovation and product enhancement. CSI Solar Co., Ltd. reserves the right to make necessary adjustment to the information described herein at any time without notice.

Caution: For professional use only. The installation and handling of PV equipment requires professional skills and should only be performed by qualified professionals. Please read the safety and installation instructions before using the product.

CSI SOLAR CO., LTD.

199 Lushan Road, SND, Suzhou, Jiangsu, China, 215129 www.csisolar.com

May 2021, All rights reserved. PV Inverter Product Datasheet V1.8_EN